# **Desktop Card Printer**

from NBS Technologies

# **Javelin® DNA**

The Javelin® DNA is our NEW generation, streamlined desktop card printer with built-in input hopper, output stacker and all the added options for your personalization needs. This compact and powerful model is user-friendly and delivers outstanding performance for instant results at a great price.

Javelin® DNA offers an all in one solution with high quality colour or monochrome printing for single sided to dual sided field upgrade option. This new upgrade provides many security lock and upgrade selections such as wifi, and encoding modules.

### **IDEAL APPLICATION FOR IDENTIFICATION AND ACCESS, INSTANT BANKING ISSUING, HOSPITALITY POWER IN A B**

With your Javelin® DNA, the following accessories are included:

- YMCKO Roll
- **USB** Cable
- Card Cleaning Kit
- Javelin Designer Create Software



#### THE JAVELIN® DNA OFFERS THESE KEY FEATURES AND BENEFITS:



#### **FLEXIBLE**

- Dual sided field upgrade
- Compact and streamlined desktop format
- Security lock options
- 16.7 million colour options
- Wifi option

ECHNOLOGIE



#### **NETWORKING AND ENCODING**

- Contact & contactless smart card encoding capabilities
- Internal USB hub to connect camera, memory stick and other peripheral devices
- 3-track magnetic strip encoding (HiCo-LoCo)



#### **EASY-TO-USE**

- ID card software and consumables included with printer
- LCD screen displays printer status and diagnotics
- Easy to change ribbon and thermal print head

CONSULTING	SOFTWARE	HARDWARE	SMART CARD EQUIPMENT
Tota			







## **Javelin® DNA**

Stanuaru Kiusk			
Print Mode	Single or dual sided printing (option: dual-sided printing)		
Print Method	Thermal transfer (mono), Dye-sublimation (colour)		
Print Speed	Mono: 800 cph, YMCKO: 180-200 cph, (single-side) YMCKOK: 100 cph (dual-sided)		
Ribbons	KrO: 500 prints/roll, YMCKO: 200 prints/roll, YMCKOK: 170 prints/roll Half-panel YMC plus full-panel KO:500 prints/roll Monochrome: black, silver, gold, red, blue, white, green: 1000 prints/roll		
Card encoding op- tions	Magnetic Stripe: ISO7811(tracks 1, 2, 3); Hi-Co/Lo-Co, Head life 4,000,000 passes Contact (IC): ISO 7816, EMV, PC/SC, IC contact life: 1,000,000 passes Contactless(RF) MiFare, ISO 14443 A,B ISO15693		
Warranty	30 months		
Printer interfaces	USB 2.0 Internal USB hub to connect peripheral devices		
Software drivers	Windows XP, Server 2003/2008, Vista, Windows7, Windows 8 &10		
Fonts/Images	300 dpts per inch (11.8 dots per mm) resolution, 16.7 million colours True Type fonts via Windows drivers		
Barcodes	Code 39, Code 128 B&C with & without check digit. 2 of 5 interleaved UPC-A, EAN 8 & EAN 13 PDF-417 2D barcode adn other symbols can be printed via Windows drivers		
Card capacity	Input hopper: 100 cards (.076mm), Output hopper: 60 cards(.076mm)		
Power source	input: 100V-240V, 50/60Hz; Output: DC24V, 2.5A (FCC Class A, CE and CCC ,KCC, Energy Star approved)		
Dimensions	Single-side 305.6mm(L) x 184mm(L) x 228mm(H)	Dual-side 366mm(L) x 184mm(L) x 228mm(H)	
Weight	Single-side 3.7kg / 8.16lbs	Dual-side 4.5kg / 9.92	
CPU & RAM	CPU: 32 bit processor RAM: 128MB		
Environment	Operating temperature: 5-40°C / 41 - 104°F, 20-65% Storage temperature: -10 - 60°C / 14 - 140°F	RH	

#### **Card Specifications**

**Standard Kiosk** 

 Types
 PVC & composite PVC

 Card width/length
 ISO CR-80-ISO 7810 (53.98mm (W) x 85.60mm (L)

 Card thickness
 0.4mm - 1.2mm



Interface for USB (high speed), built in 10/100 ethernet, Wifi (optional)



Additonal security features and dual hopper option

Contact our NBS card personalization Europe, Middle East, Africa experts for full details on this and other B1 Moorfield Point

Slyfield Industrial Park

United Kingdom tel: +44 (0)1483 563200 fax: +44 (0)1483 511189

Guildford, Surrey GU1 1RU

card personalization products at:



Easy to read 4 line LCD screen for clear notifications and prompts

North / South America 10925 Bren Road E

tel: +1 416.840.8620 fax: +1 952.912.9439

USA

Minneapolis, MN 55343



Asia Pacific PO Box 780 Hurstville BC NSW 1481 Australia tel: +61 (2) 9546 6841 fax: +61 (2) 9546 6851



e: javelin@nbstech.com

@April 2016 NBS Technologies Inc. Specifications are subject to change without notice. All rights reserved. NBS and the NBS logo are registered trademarks of NBS Technologies Inc. in the United States and Canada. Javelin & Javelin logo are trademarks of NBS Technologies Inc. with registration in the USA and the European Union.